

Range of Crosslinked Polyethylene Pipes


GPF TERM PE-Xa S. 4.0-5.0

PE-Xa PIPE SERIES 4.0-5.0
UNE EN ISO 15875-2 STANDARD
AENOR  CERTIFICATE
WHITE

CODE	DIMENSION	M/COIL
339001	16 (1.8)	100
339002	20 (1.9)	100
339003	25 (2.3)	50
339004	32 (2.9)	50




PE-Xb FERROPLAST S. 4.0-5.0

PE-Xb PIPE SERIES 4.0-5.0
UNE EN ISO 15875-2 STANDARD
AENOR  CERTIFICATE
WHITE

CODE	DIMENSION	M/COIL-BAR
216002	16 (1.8)	100
216020	16 (1.8)	200
216021	16 (1.8)	4
216003	20 (1.9)	100
216022	20 (1.9)	120
216023	20 (1.9)	200
216024	20 (1.9)	4
216015	25 (2.3)	50
216025	25 (2.3)	120
216026	25 (2.3)	4
216008	32 (2.9)	50
216027	32 (2.9)	4
216009	40 (3.7)	50
216028	40 (3.7)	4
216010	50 (4.6)	50
216029	50 (4.6)	4
216054	63 (5.8)	4
216055	75 (6.8)	4
216056	90 (8.2)	4




FERROPLAST PE-Xb S. 3.2 AND SPECIAL

PE-Xb PIPE SERIES 3.2 AND SPECIAL MEASUREMENTS
UNE EN ISO 15875-2 STANDARD
AENOR  CERTIFICATE
WHITE

CODE	DIMENSION	M/COIL-BAR
216001	12 (1.7)	100
216043	12 (2.0)	100
216044	16 (2.0)	100
216004	16 (2.2)	100
216030	16 (2.2)	4
216045	20 (2.0)	100
216005	20 (2.8)	100
216031	20 (2.8)	4
216006	25 (3.5)	50
216032	25 (3.5)	4
216007	32 (4.4)	50
216033	32 (4.4)	4



FERROPLAST PE-Xb EVOH

PE-Xb OXYGEN DIFFUSION BARRIER EVOH PIPE
UNE EN ISO 15875-2 STANDARD
AENOR  CERTIFICATE
WHITE

CODE	DIMENSION	M/COIL
232002	16 (1.8)	120
232003	16 (1.8)	200
232014	16 (1.8)	400
232009	16 (1.8)	500
232004	20 (1.9)	120
232005	20 (1.9)	200



FERROPLAST PRE-INSULATED PE-Xb

PE-Xb PRE-INSULATED PIPE
UNE EN ISO 15875-2 STANDARD
AENOR  CERTIFICATE
TRANSPARENT CORRUGATED
PIPE IN RED AND BLUE COLOURS

CODE	DIMENSION	M/COIL
241011	16 (1.8) RED	100
241012	16 (1.8) BLUE	100
241010	16 (1.8) DUO	50
241005	20 (1.9) RED	60
241006	20 (1.9) BLUE	60
241007	25 (2.3) RED	60
241008	25 (2.3) BLUE	60

